

AVR - CO2 CAPTURE AND LIQUEFACTION

Juliana Monteiro, Purvil Khakharia, Joris Koornneef

TNO innovation
for life


AVR
energy inside.

This project is supported with Topsector Energiesubsidies of the Ministry of Economic Affairs

BIO-CCUS PROJECTS


AVR Duiven

- › Feasibility study for CO₂ capture from waste to energy plant
- › 50,000 tCO₂/yr
- › Delivery of CO₂ captured to horticulture by truck




SETTING THE SCENE

- › Waste to energy plant AVR Duiven
- › Main supplier of district heating network
- › 70 MW_{th}
- › Waste (54% bio / sustainable)
- › Paper pulp residu (100% sustainable)
- › Electricity to grid: 125 GWh
- › Heat to grid: 880 TJ (14.000 households)



SETTING THE SCENE


- › Approximately 0.2 Mtonnes of fossil CO₂ / year
- › Aim to recover 50,000 tCO₂/yr
- › Supply the gas to horticulture in the regional market
- › Upscaling towards 2030
- › Improving overall footprint significantly



SETTING THE SCENE

- › Horticulture: local combined heat-and-power stations not economical to produce CO₂ for growth enhancement themselves,
- › CO₂ and costs are saved.
- › External CO₂ supply enables horticulture to make a shift towards renewable energy use for heating,

Seasons CO₂ & Heat




PHASED APPROACH

PHASE 1	CONCEPTUAL DESIGN	
WP 1	User requirements	D01. User Requirements Report
WP 2	Conceptual process design <ul style="list-style-type: none"> • Technology Selection • Process Flow Diagram • Integrated design • Technical/economic evaluation • Implementation roadmap, Risk identification and reporting 	D02. Conceptual Design Report including initial Development Plan
PHASE 2	SMALL SCALE TEST	
WP 3	Small scale test and validation	D03. Test and validation Report Test results include measurements on solvent degradation, emissions and CO ₂ -quality.
WP 4	Final reporting – including development plan	D04. Final report - updated D02 report including development plan

› SOME FIRST INSIGHTS




CO₂ CAPTURE AND LIQUEFACTION



FLUE GAS

- › 102 000 Nm³/h
- › 10% CO₂ (dry basis) = 7,6% CO₂ (wet basis)
- › Design basis: capture 12 ton/h (full load = 78% capture)
 - › Flex: Operate at 50% and 80% load + Determine maximum throughput



FLUE GAS CONDITIONING AND CO2 CAPTURE

Flue gas:

- Too hot
- Not enough pressure

Blower

Quench

Absorber

Stripper

Distillation
and flash

- Cooling water

- Offgas to
water wash

- CO2 to
liquefaction


SUMMARY – INDICATIVE NUMBERS

- › Flue gas conditioning + CO₂ capture

- › Utilities and consumables :
 - › Electricity = 17-21 kWh/ton CO₂
 - › Cooling water = ~1500-2500 m³/h
 - › Steam = 3-4 GJ/ton CO₂
 - › MEA to be determined

- › CAPEX: to be determined

CO₂ LIQUEFACTION PLANT



› NEXT STEPS



TNO MOBILE PILOT PLANT THIS SUMMER



FINAL REPORT
SEPTEMBER 2016

QUESTIONS?

